

Coating Unit Cleaner Offset

The Coating Unit Cleaner is a fully automatic system for cleaning of one anilox and one chamber from the lacquering station on the offset press.

The machine is easy to operate and will leave the anilox and chamber clean in only 15-20 minutes. After cleaning the items are ready for immediate reuse or storage.

The Coating Unit Cleaner is controlled by a micro-processor, which makes it easy to set the different programmes e.g. wash time.

Safe, Quick and Easy Cleaning:

1. Place the anilox and chamber in the machine
2. Set required washing time and press start
3. The anilox and chamber are cleaned by an environmentally friendly liquid
4. At the end of the wash cycle the cleaning liquid is drained back to tank for reuse.
5. The automatic rinse cycle starts
6. After rinsing the drying process starts.
7. The machine will stop automatically after ended rinse cycle.



	Coating Unit Cleaner Offset
Machine Dimensions LxWxH*	1835 x 970 x 1950 mm
Number of Rolls	1
Max. Roll Diameter	Ø 230 mm
Max. Roll Length (incl. shaft)	1350 mm
Max. Cleaning Length	1210 mm
Chamber size	1450 x 390 mm
Control System	Microprocessor
Power Supply	3x400V+N+PE, 50 Hz, 16 Amps

* Height with lid open

